

TW series – Thru Wall condensing units

- Insulated for indoor sound attenuation
- Installed and serviced from the indoors
- 208 / 230V single phase
- G90 Galvanized for long rust-free life
- Wall sleeves have insulated back panel to ensure air tight seal and avoid cold migration through AC unit in winter.

TW



Catalogue No.	Capacity (Tons)	Cabinet dimensions (inches)			Refrigerant Line size		Electrical	
		Width	Height	Depth	Liquid	Vapor	Min Amps	Max Breaker Amps
TW08	0.75	14.25	56	16	3/8"	5/8"	6	15
TW12 ⁽¹⁾	1.0	14.25	56	16	3/8"	5/8"	8	15
TW18 ⁽¹⁾	1.5	14.25	56	16	3/8"	5/8"	11	15
TW-sleeve	-	14.5	58.75	18.25	-	-	-	-
TW-grille	-	14.5	58.75	1	-	-	-	-

- (1) These models available on Reliance Rental Program
- (2) Model sizes subject to change. Refer to latest spec and time of order.
- (3) Wall grilles available in brushed aluminum or 4 standard colors. Custom paint color available for large orders.
- (4) For wall sleeve Rough Opening size, add ¼ to ½ inch to outside dimensions shown.
- (5) All 0.75, 1.0 and 1.5 Ton models are tested as Through the Wall (TTW) central air conditioners at >12.0 SEER in accordance with CSA C656-05 in compliance with GOC SOR/2019-163 June 3, 2019 and O. Reg. 509/18

TWF & TWH series – Thru Wall condensing units

- Insulated for indoor sound attenuation
- Installed and serviced from the indoors
- 208 / 230V single phase
- G90 Galvanized for long rust-free life
- TWF wall sleeve and grille painted matching beige.
- Wall sleeves have insulated back panel to ensure air tight seal and avoid cold migration through AC unit in winter.

TWF



Catalogue No.	Capacity (Tons)	Cabinet dimensions (inches)			Refrigerant Line size		Electrical	
		Width	Height	Depth	Liquid	Vapor	Min Amps	Max Breaker Amps
TWF08	0.75	23.75	31.5	18.75	3/8"	5/8"	6	15
TWF12 ⁽¹⁾	1.0	23.75	31.5	18.75	3/8"	5/8"	8	15
TWF18 ⁽¹⁾	1.5	23.75	31.5	18.75	3/8"	5/8"	11	15
TWF24 ⁽⁵⁾	2.0	23.75	31.5	18.75	3/8"	3/4"	15	20

TWF-sleeve	-	24	32	21.25	-	-	-	-
TWF-grille	-	24	32	1	-	-	-	-

- (1) These models are available on Reliance Rental Program
- (2) Model sizes subject to change. Refer to latest spec and time of order.
- (3) Wall grilles available in brushed aluminum or 4 standard colors. Custom paint color available for large orders.
- (4) For wall sleeve Rough Opening size, add ¼ to ½ inch to outside dimensions shown.
- (5) TWF24 is designed for use in retrofit applications only.
- (6) All 0.75, 1.0 and 1.5 Ton models are tested as Through the Wall (TTW) central air conditioners at >12.0 SEER in accordance with CSA C656-05 in compliance with GOC SOR/2019-163 June 3, 2019 and O. Reg. 509/18